

Certificate of Constancy of Performance

No. 0780-CPR-224029

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR), this certificate applies to the construction products

VECU-STOP, VS-P80/2:15/110

redirective crash cushion, to be applied in traffic areas
(Specified on page 2)

placed on market by

SPS-Schutzplanken GmbH
Hinterm Waldcasino 2
63762 Großostheim-Ringheim
GERMANY

And produced at the
manufacturing plant

Bozem Stahlbau GmbH
Hinterm Waldcasino 2
63762 Großostheim-Ringheim
Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the harmonised standard

EN 1317-5:2007 +
A2:2012/AC:2012

Road Restraint Systems

under system 1 for the performances set out are applied and that the construction products fulfil all the prescribed requirements for these performances.

This certificate replaces the certificate with identic number issued 15.07.2022, first issued 2022-05-23. It will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction products, and the manufacturing conditions in the plant are not modified significantly, latest until 2030-10-27, unless suspended or withdrawn by the FPC certification body.

Nuremberg, 2025-10-27


Dipl.-Ing. (FH) Günther Jost
Head of certification body



Certificate of Constancy of Performance

No. 0780-CPR-224029

Page 2 of 2 of the certificate of constancy of performance dated 2025-10-27

Certified construction products: **VECU-STOP, VS-P80/2:15/110**

Redirective crash cushion, to be applied in traffic areas

Material: steel S235 JRG2

Performances related to the essential characteristics acc. EN 1317-5, Annex ZA

Performance under vehicle impact Restraint category (<i>former velocity class</i>) Impact severity level Vehicle redirection (class) Displacement <u>zone</u> (class)	(according to group test matrix Test report 22S00026, dated 2022-05-10) and addendum 22S00029, dated 2022-07-11 110 km/h A Z3 D1 
Durability	structural steel S235JR galvanized in accordance with EN ISO 1461

